



NEW SOUNDWALL™ X-BASE ALL-WEATHER SPECIFICATION

Specifications	XBW600 AW	XBC600 AW	XBC800 AW
Construction	Front plastic ABS frame	Front plastic ABS frame	Front plastic ABS frame
Drive units	Woofers: 6.5" pp protected cone 1.1" voice coil, ferrite magnet motor. Tweeter: 1" soft dome, neodymium magnet motor	Woofers: 6.5" pp protected cone 1.1" voice coil, ferrite magnet motor. Tweeter: 1" soft dome, neodymium magnet motor	Woofers: 8" pp protected cone 1.1" voice coil, ferrite magnet motor. Tweeter: 1" soft dome, neodymium magnet motor
Nominal impedance	4ohm	4ohm	4ohm
Sensitivity 2.83V/1M	90dB	90dB	91.5dB
Power handling	90W(RMS)	80W(RMS)	100W(RMS)
Operating power	20-100W	10-70W	10-100W
Crossover	3,500Hz / 12dB	4,500Hz / 6dB	3,500Hz / 12dB
Frequency response	50-22,000Hz (-5dB)	55-20,000Hz (-5dB)	45-20,000Hz (-5dB)
Grille	Metal - water resistant E-Coating	Metal - water resistant E-Coating	Metal - water resistant E-Coating
Overall exterior grille dimensions (WxHxD/ø)	8.4"x11.8" (212x300mm)	8.9" (228mm)	11.1" (282mm)
Cut out dimensions (HxW/ø)	7.3"x10.7" (185x273mm)	8.1" (206mm)	9.7" (246mm)
Mounting Depth	3.15" (80mm)	3.15" (80mm)	3.9" (100mm)
Grill Finish	white	white	white